

# FILTRES À TAMIS

## FYBT 202



### Filtre Y Bronze Taraudé

- > Corps : Bronze | > Tamis : AISI304
- > Joint : PTFE
- > Filtration 4/10° du 3/8" au 1" puis 5/10° jusqu'au 4" - Montage horizontal ou vertical



Diamètre	PS bar	FAF mm	Référence
3/8"	16	55	9010415
1/2"	16	59	9010416
3/4"	16	69	9010417
1"	16	82	9010418
1"1/4	16	99	9010419
1"1/2	16	109	9010420
2"	16	131	9010421
2"1/2	10	151	9010422
3"	10	172	9010423
4"	10	219	9010424

## FYLT 206



### Filtre Y Laiton Taraudé

- > Corps : Laiton CW617N | > Tamis : AISI304
- > Joint : EPDM
- > Filtration 8/10° - Montage horizontal ou vertical



Diamètre	PS bar	FAF mm	Référence
3/8"	16	48	9670685
1/2"	16	58	9670686
3/4"	16	68	9670687
1"	16	75	9670688
1"1/4	16	90	9670689
1"1/2	16	108	9670690
2"	16	130	9670691

## FYLT 211



### Filtre Y Laiton Taraudé

- > Corps : Laiton CW617N | > Tamis : AISI304
- > Joint : EPDM
- > Filtration 8/10° - Montage horizontal ou vertical descendant - Avec robinet de purge



Diamètre	PS bar	FAF mm	Référence
1/2"	16	58	9748664
3/4"	16	68	9723026
1"	16	75	9748661
1"1/4	16	90	9748663
1"1/2	16	108	9748662
2"	16	130	9748665

## FYAT FIG14



### Filtre Y Acier Taraudé

- > Corps : Acier Carbone | > Tamis : 316L
- > Joint : Graphite
- > Filtration 8/10° - Montage horizontal ou vertical



Diamètre	PS bar	FAF mm	Référence
1/4"	35	70	9002957
3/8"	35	70	9002958
1/2"	35	73	9002959
3/4"	35	90	9002960
1"	35	105	9002961
1"1/4	35	140	9002962
1"1/2	35	152	9002963
2"	35	178	9002964

## FYAT 231



### Filtre Y Acier Taraudé

- > Corps : ASTM A105N | > Tamis : ASTM A240 316L
- > Joint : Graphite
- > Filtration 8/10° - Montage horizontal ou vertical descendant



Diamètre	PS bar	FAF mm	Référence
1/4"	75	90	9748658
3/8"	75	90	9748660
1/2"	75	90	9748657
3/4"	75	110	9670002
1"	75	130	9748654
1"1/4	75	160	9748656
1"1/2	75	160	9748655
2"	75	160	9748659

## FYIT 230



### Filtre Y Inox Taraudé

- > Corps : 1.4408 | > Tamis : AISI304
- > Joint : PTFE
- > Filtration 10/10° - Montage horizontal ou vertical descendant - Bouchon avec purge démontable  
Ne convient pas pour la vapeur



Diamètre	PS bar	FAF mm	Référence
1/4"	16	64	9201679
3/8"	16	64	9201683
1/2"	16	64	9201684
3/4"	16	80	9015426
1"	16	89	9201685
1"1/4	16	106,5	9201686
1"1/2	16	118	9201687
2"	16	139	9201688

# FILTRES À BRIDE

## FYFB 220



### Filtre Y Fonte à Bride

- > Corps : Fonte EN GJL-250 | > Tamis : AISI304
- > Joint : Graphite
- > Perforation 1,2 à 3 mm en fonction des DN  
Montage horizontal ou vertical descendant



DN	PS bar	FAF mm	Référence
15	16	130	9010425
20	16	150	9010426
25	16	160	9010428
32	16	180	9010429
40	16	200	9010431
50	16	230	9010432
65	16	290	9010434
80	16	310	9010438
100	16	350	9010440
125	16	400	9010442
150	16	480	9010444
200	16	600	9010446
250	10	730	9010449

## FYFB FIG33



### Filtre Y Fonte à Bride

- > Corps : Fonte GG20 | > Tamis : ASTM A240 316L
- > Joint : Graphite
- > Perforation 0,8 mm du DN15 à 80, 1,6 mm DN100 à 200 -  
Montage horizontal ou vertical descendant



spirax/sarco

DN	PS bar	FAF mm	Référence
15	13	130	135637
20	13	150	135638
25	13	160	135639
32	13	180	135640
40	13	200	135641
50	13	230	135642
65	13	290	9055220
80	13	310	9055221
100	13	350	9055222
125	13	400	9055223
150	13	480	9055224
200	13	600	9055225

## FYFB 236



### Filtre Y Fonte à Bride

- > Corps : Fonte EN GJL-250 | > Tamis : ASTM A182F 304
- > Joint : Graphite
- > Perforation de 1 à 1,6 mm en fonction du DN  
Montage horizontal ou vertical descendant -  
Bouchon de purge - Pression vapeur 10 bar max



DN	PS bar	FAF mm	Référence
15	16	130	9709691
20	16	150	9709693
25	16	160	9709695
32	16	180	9709696
40	16	200	9709697
50	16	230	9709698
65	16	290	9709699
80	16	310	9709700
100	16	350	9709689
125	16	400	9709690
150	16	480	9709692
200	16	600	9709694

## FYAB FIG34



### Filtre Y Acier à Bride

- > Corps : Acier 1.0619+N | > Tamis : ASTM A240 316L
- > Joint : Graphite
- > Perforation 0,8 mm du DN15 à 80, 1,6 mm DN100 à 200 -  
Montage horizontal ou vertical descendant



spirax/sarco

DN	PS bar	FAF mm	Référence
15	22	130	9002965
20	22	150	9002966
25	22	160	9002967
32	22	180	9002968
40	22	200	9002969
50	22	230	9002970
65	22	290	9055226
80	22	310	9055227
100	22	350	9055228
125	22	400	9055229
150	22	480	9055230
200	22	600	9055231

## FYAB 235



### Filtre Y Acier à Bride

- > Corps : Acier ASTM A216WCB | > Tamis : AISI304
- > Joint : Graphite
- > Perforation de 1 à 1,6 mm en fonction du DN - Montage  
horizontal ou vertical descendant - Bouchon de purge



DN	PS bar	FAF mm	Référence
15	18	130	9742645
20	18	150	9742646
25	18	160	9742647
32	18	180	9742656
40	18	200	9742648
50	18	230	9742649
65	18	290	9742650
80	18	310	9742651
100	18	350	9742652
125	18	400	9742653
150	18	480	9742654
200	18	600	9742655

## FYIB 240



### Filtre Y Inox à Bride

- > Corps : Inox EN 1.4408 | > Tamis : AISI304
- > Joint : PTFE
- > Perforation de 0,8 à 3 mm en fonction du DN - Montage  
horizontal ou vertical descendant - Bouchon de purge



DN	PS bar	FAF mm	Référence
15	16	130	9201689
20	16	150	9201690
25	16	160	9201691
32	16	180	9201692
40	16	200	9201693
50	16	230	9081021
65	16	290	9201694
80	16	310	9201695
100	16	350	9201696
125	16	400	9201697
150	16	480	9201698
200	16	600	9201699